

D342X/PTFE/PPL 蜗轮法兰蝶阀（双偏心）

规格	L	H	H1	1.0Mpa					1.6Mpa					2.5Mpa				
				ØD	ØD1	ØD2	n-Ød	b	ØD	ØD1	ØD2	n-Ød	b	ØD	ØD1	ØD2	n-Ød	b
DN50	108	320	85	165	125	99	4-Ø18	20	165	125	99	4-Ø18	20	165	125	99	4-Ø18	20
DN65	112	370	90	185	145	118	4-Ø18	20	185	145	118	8-Ø18	20	185	145	118	8-Ø18	20
DN80	114	370	100	200	160	132	8-Ø18	20	200	160	132	8-Ø18	20	200	160	132	8-Ø18	20
DN100	127	370	125	220	180	156	8-Ø18	22	220	180	156	8-Ø18	22	235	190	156	8-Ø22	24
DN125	140	420	135	250	210	184	8-Ø18	22	250	210	184	8-Ø18	22	270	220	184	8-Ø26	26
DN150	140	505	172	285	240	211	8-Ø22	24	285	240	211	8-Ø22	24	300	250	211	8-Ø26	28
DN200	152	610	240	340	295	266	8-Ø22	24	340	295	266	12-Ø22	24	360	310	278	12-Ø26	30
DN250	165	665	265	395	350	319	12-Ø22	26	405	355	319	12-Ø26	26	425	370	332	12-Ø30	32
DN300	178	755	295	445	400	370	12-Ø22	26	460	410	370	12-Ø26	28	485	430	390	16-Ø30	34
DN350	190	860	330	505	460	429	16-Ø22	26	520	470	429	16-Ø26	30	565	490	448	16-Ø33	38
DN400	216	890	370	565	515	480	16-Ø26	26	580	525	480	16-Ø30	32	620	550	505	16-Ø36	40
DN450	222	966	395	615	565	530	20-Ø26	28	640	585	548	20-Ø30	34	670	600	555	20-Ø36	42
DN500	229	1040	430	670	620	582	20-Ø26	28	715	650	609	20-Ø33	36	730	660	610	20-Ø36	44
DN600	267	1285	490	780	725	682	20-Ø30	34	840	770	720	20-Ø36	38	845	770	720	20-Ø39	46
DN700	292	1395	545	895	840	794	24-Ø30	34	910	840	794	24-Ø36	40	960	875	820	24-Ø42	46
DN800	318	1560	615	1015	950	901	24-Ø33	36	1025	950	901	24-Ø39	42	1085	990	930	24-Ø48	50
DN900	330	4700	700	1115	1050	1001	28-Ø33	38	1125	1050	1001	28-Ø39	44	1185	1090	1028	28-Ø48	58
DN1000	410	1865	715	1230	1160	1112	28-Ø36	38	1255	1160	1112	28-Ø42	46	1320	1210	1140	28-Ø55	62
DN1200	470	2125	865	1455	1380	1328	32-Ø39	44	1485	1380	1328	32-Ø45	52	1530	1420	1350	32-Ø55	70